

ECOAT SOLUTIONS

PRODUCT DATA SHEET

ECS 2620

NANO-CERAMIC INDUSTRIAL MOLD REPAIR COATING

ECS 2620 - eCoat Mold Repair coating rejuvenates and repairs all types of industrial molds. ECS 2620 permanently fills and seals pinholes and micro-cracks on the face side of almost any mold. Ultra-thin application means no change to the mold dimensions. ECS 2620 significantly improves the ROI for any molding tool by extending the useful life of the mold and repairing molds that would otherwise be inoperable. Available with optional black light tracer to enable easy inspection of coating coverage.

Proudly manufactured in the USA.

Technical Data

| | |
|--|------------------------------------|
| Color | Clear |
| Viscosity | 16 - 18 sec. #2 Zahn |
| Percent of Solids (%) | 18 |
| V.O.C | Exempt per CFR 51.1 / Regulation 8 |
| RoHS | Compliant |
| REACH | Compliant |
| Halogens | None |
| Thermal Stability (cured) | 1200°F (648.8°C) |
| Conical Bond (1/8" Mandrel) (ASTM D522-93a) | Passed |
| Cross Cut Adhesion (ASTM D3359) | 5B |
| Coefficient of Friction (ASTM D2047) | 0.03μ |
| Specific Gravity (ASTM D891-09) | 0.889 |
| Pencil Hardness (ASTM D3363) | 8h |
| Odor (liquid) | Slight Solvent |
| Odor (cured) | None |

Drying and Coverage Rate

| | |
|--|--|
| Average Applied Dry Film Thickness | 2 to 5 microns |
| Estimated Coverage Rate (@ 3 microns) | 2,450 ft ² (230 m ²) per gallon |
| Dry to Touch Time (@ 77°F / 25°C) *Exposure to a warmer air flow (not exceeding 110°F) will accelerate drying and curing | 15 – 25 minutes (average) |
| Ambient Cure (Full Properties) | 5 days |

Key Performance Properties

- High performance single component mold sealer.
- Restores expensive leaking molds of all kinds to full working condition.
- Permanently fills and seals pinholes and micro-cracks from the face side of the mold tool.
- Creates a covalent bond to the substrate giving it an intrinsic bond to the mold. Soaks into the substrate as opposed to merely sitting on the surface.
- Ultra thin coating will not change mold dimensions.
- Easy application by wipe and ambient cure.
- VOC exempt coating.
- Inert (benign) material containing no free silicones.
- RoHS and REACH compliant.

Common Applications

All common mold tools.

Supplemental Information

ECS 2620(BL) is available with black light tracer for easily inspecting coating coverage once applied.

ECOAT LLC – 12055 41ST AVENUE NORTH # 218, PLYMOUTH, MINNESOTA 55441
 INFO@ECO-COATSOLUTIONS.COM – 612.314.3999 – WWW.ECO-COATSOLUTIONS.COM

THE INFORMATION CONTAINED HEREIN IS BELIEVED BY ECOAT LLC TO BE ACCURATE AND IS OFFERED SOLELY FOR THE CUSTOMER'S CONSIDERATION, INVESTIGATION, AND VERIFICATION. DETERMINATION OF SUITABILITY FOR USE IS THE RESPONSIBILITY OF THE USER. ECOAT LLC'S LIMITATIONS, LIMITED WARRANTY, & DISCLAIMER ALONG WITH STANDARD TERMS & CONDITIONS APPLY. SEE WWW.ECO-COATSOLUTIONS.COM FOR MORE INFO. LIMITATIONS: STANDARD VARIATIONS OF MECHANICAL PROPERTIES AND HYDRAULIC PROPERTIES ARE NORMAL. ECOAT PRODUCTS ARE RESISTANT TO CHEMICALS IN NORMAL ENVIRONMENTS, HOWEVER SOME REAGENTS MAY AFFECT THE PERFORMANCE OF THESE PRODUCTS. AN ECOAT REPRESENTATIVE SHOULD BE CONTACTED FOR FURTHER INFORMATION TO DETERMINE THE SUITABILITY OF USE OF THESE PRODUCTS IN UNUSUAL ENVIRONMENTS. UNLESS OTHERWISE STATED, ECOAT PRODUCTS SHOULD HAVE LIMITED EXPOSURE TO ARTIFICIAL UV AND SUNLIGHT. ECOAT'S PRODUCTS SHOULD BE PROTECTED IMMEDIATELY, AND IF APPLICABLE, COVERED FOR 48 HOURS AFTER INSTALLATION TO PROTECT FROM MOISTURE. DISCLAIMERS: ALL INFORMATION, DRAWINGS AND SPECIFICATIONS ARE BASED ON THE LATEST PUBLISHED INFORMATION AT THE TIME OF PRINTING. ECOAT LLC RESERVES THE RIGHT TO MAKE CHANGES DUE TO MANUFACTURING IMPROVEMENTS AND ENGINEERING AT ANY TIME. ALL PHYSICAL PROPERTIES ARE MINIMUM AVERAGE VALUES (MAV).